
django-permissions-auditor **Documentation**

Release 0.4.2

Christian Klus

Jan 23, 2019

Contents:

1	Features	3
2	Installation	5
2.1	Contribute	5
2.2	License	5

Admin site for auditing and managing permissions for views in your Django app.

Django administration

WELCOME, ADMIN VIEW SITE / CHANGE PASSWORD / LOG OUT

Home · Permissions Auditor · Site Views

Views By Module

django.contrib.staticfiles.views

NAME	URL	PERMISSION REQUIRED	LOGIN REQUIRED	ADDITIONAL INFO
serve	/staticV<path>		🔴	

test_app.views

NAME	URL	PERMISSION REQUIRED	LOGIN REQUIRED	ADDITIONAL INFO
home_page	/		🟢	
LoginPage	/accounts/login/		🔴	
LogoutPage	/accounts/logout/		🔴	

test_app.views.cbv_based

NAME	URL	PERMISSION REQUIRED	LOGIN REQUIRED	ADDITIONAL INFO
UserIndex	/cbv/users/	auth.view_user	🟢	PermissionRequiredMixin - Docstrings on 'has_permission()' are displayed in the admin.
SuperUserIndex	/cbv/super_users/		🔴	UserPassesTestMixin - The user must be a superuser to access.
PermissionsIndex	/cbv/permissions/	auth.view_user auth.change_user	🟢	

test_app.views.function_based

NAME	URL	PERMISSION REQUIRED	LOGIN REQUIRED	ADDITIONAL INFO
user_index	/func/users/	auth.view_user	🟢	
superuser_index	/func/super_users/		🟢	Superuser required
permissions_index	/func/permissions/		🟢	Staff member required

FILTER

Group By

Module

Permission

No Grouping

Navigate

django.contrib.staticfiles.views

test_app.views

test_app.views.cbv_based

test_app.views.function_based

CHAPTER 1

Features

- Automatically parse views registered in Django's URL system
- Out of the box support for Django's authentication system
- Easily extensible for custom permission schemes

Requirements:

- Django >=2.1
- Python 3.5, 3.6, 3.7

To install:

```
pip install django-permissions-auditor
```

Add *permissions_auditor* to your `INSTALLED_APPS` in your project's `settings.py` file:

```
INSTALLED_APPS = [  
    ...  
    'permissions_auditor',  
    ...  
]
```

2.1 Contribute

- Issue Tracker: <https://github.com/AACEngineering/django-permissions-auditor/issues>
- Source Code: <https://github.com/AACEngineering/django-permissions-auditor>

2.2 License

The project is licensed under the MIT license.

2.2.1 Overview

In large Django applications that require complex access control, it can be difficult for site administrators to effectively assign and manage permissions for users and groups.

I often found that I needed to reference my site's source code in order to remember what permission was required for what view - something end-users and managers shouldn't need to do.

Django-permissions-auditor attempts to solve this problem by automatically parsing out permissions so that administrators can easily manage their site.

2.2.2 Installation

Requirements:

- Django >=2.1
- Python 3.5, 3.6, 3.7

To install:

```
pip install django-permissions-auditor
```

Add *permissions_auditor* to your `INSTALLED_APPS` in your project's `settings.py` file:

```
INSTALLED_APPS = [  
    ...  
    'permissions_auditor',  
    ...  
]
```

2.2.3 Settings

PERMISSIONS_AUDITOR_PROCESSORS

This setting is used to configure the processors used to parse views for their permissions. You can add custom processors, or remove the default ones similar to Django's middleware system.

For details on each processor, see *Included Processors*.

Default:

```
PERMISSIONS_AUDITOR_PROCESSORS = [  
    'permissions_auditor.processors.auth_mixins.PermissionRequiredMixinProcessor',  
    'permissions_auditor.processors.auth_mixins.LoginRequiredMixinProcessor',  
    'permissions_auditor.processors.auth_mixins.UserPassesTestMixinProcessor',  
    'permissions_auditor.processors.auth_decorators.  
↪PermissionRequiredDecoratorProcessor',  
    'permissions_auditor.processors.auth_decorators.LoginRequiredDecoratorProcessor',  
    'permissions_auditor.processors.auth_decorators.  
↪StaffMemberRequiredDecoratorProcessor',  
    'permissions_auditor.processors.auth_decorators.  
↪SuperUserRequiredDecoratorProcessor',  
    'permissions_auditor.processors.auth_decorators.UserPassesTestDecoratorProcessor',  
]
```

PERMISSIONS_AUDITOR_BLACKLIST

Exclude views from parsing that match the blacklist values.

Default:

```
PERMISSIONS_AUDITOR_BLACKLIST = {
    'namespaces': [
        'admin',
    ],
    'view_names': [],
    'modules': [],
}
```

namespaces URL namespaces that will be blacklisted. By default, all views in the `admin` namespace are blacklisted.

view_names Fully qualified view paths to be blacklisted. Example: `test_app.views.home_page`.

modules Modules to be blacklisted. Example: `test_app.views.function_based`.

PERMISSIONS_AUDITOR_ADMIN

Enable or disable the Django admin page provided by the app. If `TRUE`, the admin site will be enabled. Useful if you want to create a custom management page instead of using the Django admin.

Default: `TRUE`

PERMISSIONS_AUDITOR_ROOT_URLCONF

The root Django URL configuration to use when fetching views.

Default: The `ROOT_URLCONF` value in your Django project's `settings.py` file.

PERMISSIONS_AUDITOR_CACHE_KEY

The cache key prefix to use when caching processed views results.

Default: `'permissions_auditor_views'`

PERMISSIONS_AUDITOR_CACHE_TIMEOUT

The timeout to use when caching processed views results.

Default: `900`

2.2.4 Admin Site

Once installed, you should see a *Permissions Auditor* category in your Django admin panel.

Permissions Auditor administration

PERMISSIONS AUDITOR

Groups

+ Add  Change

Site Views

 View

Note: All staff members will be able to access the site views index.

Site Views

Django administration

WELCOME, ADMIN / VIEW SITE / CHANGE PASSWORD / LOG OUT

Home > Permissions Auditor > Site Views

Views By Module

django.contrib.staticfiles.views				
NAME	URL	PERMISSION REQUIRED	LOGIN REQUIRED	ADDITIONAL INFO
serve	/staticV<path>			

test_app.views				
NAME	URL	PERMISSION REQUIRED	LOGIN REQUIRED	ADDITIONAL INFO
home_page	/			
LoginPage	/accounts/login/			
LogoutPage	/accounts/logout/			

test_app.views.cbv_based				
NAME	URL	PERMISSION REQUIRED	LOGIN REQUIRED	ADDITIONAL INFO
UserIndex	/cbv/users/	auth.view_user		PermissionRequiredMixin - Docstrings on 'has_permission()' are displayed in the admin.
SuperUserIndex	/cbv/super_users/			UserPassesTestMixin - The user must be a superuser to access.
PermissionsIndex	/cbv/permissions/	auth.view_user auth.change_user		

test_app.views.function_based				
NAME	URL	PERMISSION REQUIRED	LOGIN REQUIRED	ADDITIONAL INFO
user_index	/func/users/	auth.view_user		
superuser_index	/func/super_users/			Superuser required
permissions_index	/func/permissions/			Staff member required

FILTER

Group By

Module
Permission
No Grouping

Navigate

django.contrib.staticfiles.views
test_app.views
test_app.views.cbv_based
test_app.views.function_based

Your registered site views should display with the permissions required and any additional information in the table.

Note: If you see unexpected results, or missing permissions, ensure your *Included Processors* are correctly configured. You may need to create a custom processor if you have a view that does not use the built-in Django auth mixins

/ decorators.

When you click on a permission, you will be taken to a page which will allow you to manage what users and groups have that permission.

Permissions Management Page

Detected permissions will be automatically hyperlinked to a configuration page where you can modify what groups and users have the permission.

Django administration

WELCOME, ADMIN. [VIEW SITE](#) / [CHANGE PASSWORD](#) / [LOG OUT](#)

[Home](#) > [Permissions Auditor](#) > [auth.view_user](#)

auth.view_user

Views with this Permission				
NAME	URL	PERMISSION REQUIRED	LOGIN REQUIRED	ADDITIONAL INFO
UserIndex	/cbv/users/	auth.view_user	✓	PermissionRequiredMixin - Docstrings on 'has_permission()' are displayed in the admin.
PermissionsIndex	/cbv/permissions/	auth.view_user auth.change_user	✓	
user_index	/func/users/	auth.view_user	✓	

Permission Info

Name:

Content type:

Codename:

Objects with this Permission

Users:

Available User ?

Filter

jbrown

Choose all ?

Chosen User ?

admin
jsmith

Remove all

Groups:

Available Group ?

Filter

Choose all ?

Chosen Group ?

Employees

Remove all

[Save and continue editing](#)

[SAVE](#)

Note: In order to modify permissions on this page, the user must have the `auth.change_user` and `auth.change_group` permissions.

Groups Management Page

The default Django groups page does not let you quickly see what permissions are assigned to groups without viewing each group individually.

Django administration

WELCOME, ADMIN. VIEW SITE / CHANGE PASSWORD / LOG OUT

Home · Permissions Auditor · Groups

Select group to change ADD GROUP +

Q Search

Action: Go 0 of 3 selected

☐ NAME	PERMISSIONS	ACTIVE USERS
☐ Contractors	auth.add_group auth.add_user auth.view_user	jeff
☐ Employees	auth.change_user auth.view_user	jsmith jbrow
☐ Empty		

3 groups

Django-permissions-auditor implements a groups list containing the assigned permissions and active users.

2.2.5 Example Views

The following are example views are detected out of the box. For more examples, see `permissions_auditor/tests/fixtures/views.py`.

Simple Permission Required Page

Listing 1: views.py

```
from django.contrib.auth.mixins import PermissionRequiredMixin
from django.views.generic import TemplateView

class ExampleView(PermissionRequiredMixin, TemplateView):
    template_name = 'example.html'
    permission_required = 'auth.view_user'

    ...
```

Listing 2: urls.py

```
from django.urls import path
from views import ExampleView

urlpatterns = [
    path('', ExampleView.as_view(), name='example'),
]
```

Result:

Name	URL	Permission Required	Login Required	Additional Info
ExampleView	/	auth.view_user	True	

Custom Permission Required Page

In this example, we only want users with the first name ‘bob’ to be able to access the page.

Listing 3: views.py

```
from django.contrib.auth.mixins import PermissionRequiredMixin
from django.views.generic import TemplateView

class BobView(PermissionRequiredMixin, TemplateView):
    template_name = 'example.html'

    def has_permission(self):
        """
        Only users with the first name Bob can access.
        """
        return self.request.user.first_name == 'Bob'

    ...
```

Listing 4: urls.py

```
from django.urls import path
from views import BobView

urlpatterns = [
    path('/bob/', BobView.as_view(), name='bob'),
]
```

Result:

Name	URL	Permission quired	Re-	Login quired	Re-	Additional Info
Example-View	/bob/			True		Only users with the first name Bob can access.

Hint: The *PermissionRequiredMixinProcessor* will display the docstring on the the `has_permission()` function in the additional info column.

Simple Login Required View

Listing 5: views.py

```
from django.contrib.auth.decorators import login_required

@login_required
```

(continues on next page)

(continued from previous page)

```
def my_view(request):
    ...
```

Listing 6: urls.py

```
from django.urls import path
from views import my_view

urlpatterns = [
    path('', my_view, name='example'),
]
```

Result:

Name	URL	Permission Required	Login Required	Additional Info
my_view	/		True	

2.2.6 Included Processors

Processors are what do the work of parsing the permissions out of a view.

Django Auth Decorator Processors

PermissionRequiredDecoratorProcessor

```
class permissions_auditor.processors.auth_decorators.PermissionRequiredDecoratorProcessor
    Process @permission_required() decorator on function based views.
```

LoginRequiredDecoratorProcessor

```
class permissions_auditor.processors.auth_decorators.LoginRequiredDecoratorProcessor
    Process @login_required decorator on function based views.
```

StaffMemberRequiredDecoratorProcessor

```
class permissions_auditor.processors.auth_decorators.StaffMemberRequiredDecoratorProcessor
    Process Django admin's @staff_member_required decorator on function based views.
```

ActiveUserRequiredDecoratorProcessor

```
class permissions_auditor.processors.auth_decorators.ActiveUserRequiredDecoratorProcessor
    Process @user_passes_test(lambda u: u.is_active) decorator on function based views.
```

AnonymousUserRequiredDecoratorProcessor

```
class permissions_auditor.processors.auth_decorators.AnonymousUserRequiredDecoratorProcessor
    Process @user_passes_test(lambda u: u.is_anonymous) decorator on function based views.
```

SuperUserRequiredDecoratorProcessor

```
class permissions_auditor.processors.auth_decorators.SuperUserRequiredDecoratorProcessor
    Process @user_passes_test (lambda u: u.is_superuser) decorator on function based views.
```

UserPassesTestDecoratorProcessor

```
class permissions_auditor.processors.auth_decorators.UserPassesTestDecoratorProcessor
    Process @user_passes_test () decorator on function based views.
```

Note: the @user_passes_test decorator does not automatically check that the User is not anonymous. This means they don't necessarily need to be authenticated for the check to pass, so this processor returns None (unknown) for the login_required attribute.

Django Auth Mixin Processors

PermissionRequiredMixinProcessor

```
class permissions_auditor.processors.auth_mixins.PermissionRequiredMixinProcessor
    Processes views that directly inherit from django.contrib.auth.mixins.
    PermissionRequiredMixin.
```

Hint: If the has_permission() function is overridden, any docstrings on that function will be displayed in the additional info column.

LoginRequiredMixinProcessor

```
class permissions_auditor.processors.auth_mixins.LoginRequiredMixinProcessor
    Processes views that directly inherit from django.contrib.auth.mixins.LoginRequiredMixin.
```

UserPassesTestMixinProcessor

```
class permissions_auditor.processors.auth_mixins.UserPassesTestMixinProcessor
    Processes views that directly inherit from django.contrib.auth.mixins.UserPassesTestMixin.
```

Hint: If the function returned by get_test_func() is overridden, any docstrings on that function will be displayed in the additional info column.

Note: UserPassesTestMixinProcessor does not automatically check that the User is not anonymous. This means they don't necessarily need to be authenticated for the check to pass, so this processor returns None (unknown) for the login_required attribute.

2.2.7 Custom Processors

Base Processors

All processors inherit from `BaseProcessor`.

```
class permissions_auditor.processors.base.BaseProcessor
```

can_process (*view*)

Can this processor process the provided view?

Parameters **view** (*function or class*) – the view being processed.

Returns whether this processor can process the view. Default: `False`

Return type `boolean`

get_docstring (*view*)

Return any additional information that should be displayed when showing permission information.

Parameters **view** (*function or class*) – the view being processed.

Returns the string to display in the additional info column. Default: `None`

Return type `str` or `None`

get_login_required (*view*)

Get whether or not the view needs the user to be logged in to access.

Parameters **view** (*function or class*) – the view being processed.

Returns whether a user must be logged in to access this view. Default: `False`

Return type `boolean` or `None` (if unknown)

get_permission_required (*view*)

Get the permissions required on the provided view. Must return an iterable.

Parameters **view** (*function or class*) – the view being processed.

Returns the permissions required to access the view. Default: `[]`

Return type `list(str)`

Other useful base classes:

```
class permissions_auditor.processors.base.BaseFuncViewProcessor
```

Base class for processing function based views.

```
class permissions_auditor.processors.base.BaseCBVProcessor
```

Base class for processing class based views.

```
class permissions_auditor.processors.base.BaseFilteredMixinProcessor
```

Base class for parsing mixins on class based views. Set `class_filter` to filter the class names the processor applies to. ONLY checks top level base classes.

Variables **class_filter** – initial value: `None`

get_class_filter ()

Override this method to override the `class_names` attribute. Must return an iterable.

Returns a list of strings containing the full paths of mixins to detect.

Raises **ImproperlyConfigured** – if the `class_filter` attribute is `None`.

Parsing Mixins

Creating a custom processor for mixins on class based views is fairly straight forward.

In this example, we have a mixin `BobRequiredMixin` and a view that uses it, `BobsPage`. The mixin should only allow users with the first name Bob to access the page.

Listing 7: `example_project/views.py`

```
from django.core.exceptions import PermissionDenied
from django.views.generic import TemplateView

class BobRequiredMixin:
    def dispatch(self, request, *args, **kwargs):
        if self.request.user.first_name != 'Bob':
            raise PermissionDenied("You are not Bob")
        return super().dispatch(request, *args, **kwargs)

class BobsPage(BobRequiredMixin, TemplateView):
    ...
```

Let's define our processor in `processors.py`.

Listing 8: `example_project/processors.py`

```
from permissions_auditor.processors.base import BaseFilteredMixinProcessor

class BobRequiredMixinProcessor(BaseFilteredMixinProcessor):
    class_filter = 'example_project.views.BobRequiredMixin'

    def get_login_required(self, view):
        return True

    def get_docstring(self, view):
        return "The user's first name must be Bob to view."
```

To register our processor, we need to add it to `PERMISSIONS_AUDITOR_PROCESSORS` in our project settings.

Listing 9: `settings.py`

```
PERMISSIONS_AUDITOR_PROCESSORS = [
    ...
    'example_project.processors.BobRequiredProcessor',
]
```

When `BobsPage` is registered to a URL, we should see this in the admin panel:

Name	URL	Permission Required	Login Required	Additional Info
BobsPage	/		True	The user's first name must be Bob to view.

Perhaps we want to make our mixin configurable so we can detect different names depending on the view. We also have multiple people with the same first name, so we also want to check for a permission: `example.view_pages`.

```
class FirstNameRequiredMixin:
    required_first_name = ''
```

(continues on next page)

(continued from previous page)

```

def dispatch(self, request, *args, **kwargs):
    if not (self.request.user.has_perm('example_app.view_userpages')
            and self.request.user.first_name == self.required_first_name):
        raise PermissionDenied()
    return super().dispatch(request, *args, **kwargs)

class GeorgesPage(FirstNameRequiredMixin, TemplateView):
    required_first_name = 'George'

    ...

```

We'll modify `class_filter` and `get_docstring()` from our old processor, and override `get_permission_required()`.

```

from permissions_auditor.processors.base import BaseFilteredMixinProcessor

class FirstNameRequiredMixinProcessor(BaseFilteredMixinProcessor):
    class_filter = 'example_project.views.FirstNameRequiredMixin'

    def get_permission_required(self, view):
        return ['example.view_pages']

    def get_login_required(self, view):
        return True

    def get_docstring(self, view):
        return "The user's first name must be {} to view.".format(view.first_name_
↪required)

```

Once we register our view to a URL and register the processor, our admin table should look like this:

Name	URL	Permission quired	Re-	Login quired	Re-	Additional Info
Georges- Page	/	example.view_pages		True		The user's first name must be George to view.

Additional Examples

See the `permissions_auditor/processors/` folder in the source code for more examples.

2.2.8 Changelog

v0.4.2 (Released 1/23/2019)

- Fix permission check for groups listing (uses the default Django `'auth.change_group'`, `'auth.view_group'`)
- Fix N+1 query in groups listing

v0.4.1 (Released 1/22/2019)

- Hotfix for auth migrations issue

v0.4.0 (Release Removed)

- Add groups listing to admin site

v0.3.3 (Released 1/9/2019)

- Mark docstrings as safe in admin templates
- No longer suppress inner exceptions when parsing processors
- Fix Django admin module permissions check

v0.3.2 (Released 1/9/2019)

- Fix various cache issues
- Only show active users in the admin permission configuration page

v0.3.1 (Released 1/8/2019)

Initial stable release

A

ActiveUserRequiredDecoratorProcessor (class in permissions_auditor.processors.auth_decorators), [13](#)

AnonymousUserRequiredDecoratorProcessor (class in permissions_auditor.processors.auth_decorators), [13](#)

B

BaseCBVProcessor (class in permissions_auditor.processors.base), [15](#)

BaseFileredMixinProcessor (class in permissions_auditor.processors.base), [15](#)

BaseFuncViewProcessor (class in permissions_auditor.processors.base), [15](#)

BaseProcessor (class in permissions_auditor.processors.base), [15](#)

C

can_process() (permissions_auditor.processors.base.BaseProcessor method), [15](#)

G

get_class_filter() (permissions_auditor.processors.base.BaseFileredMixinProcessor method), [15](#)

get_docstring() (permissions_auditor.processors.base.BaseProcessor method), [15](#)

get_login_required() (permissions_auditor.processors.base.BaseProcessor method), [15](#)

get_permission_required() (permissions_auditor.processors.base.BaseProcessor method), [15](#)

L

LoginRequiredDecoratorProcessor (class in permissions_auditor.processors.auth_decorators), [13](#)

LoginRequiredMixinProcessor (class in permissions_auditor.processors.auth_mixins), [14](#)

P

PermissionRequiredDecoratorProcessor (class in permissions_auditor.processors.auth_decorators), [13](#)

PermissionRequiredMixinProcessor (class in permissions_auditor.processors.auth_mixins), [14](#)

S

StaffMemberRequiredDecoratorProcessor (class in permissions_auditor.processors.auth_decorators), [13](#)

SuperUserRequiredDecoratorProcessor (class in permissions_auditor.processors.auth_decorators), [14](#)

U

UserPassesTestDecoratorProcessor (class in permissions_auditor.processors.auth_decorators), [14](#)

UserPassesTestMixinProcessor (class in permissions_auditor.processors.auth_mixins), [14](#)